## **Instructions for Soil Evaluations**

- 1. All test holes for <u>NEW CONSTRUCTION</u> must be dug with a backhoe, by appointment <u>ONLY</u>. Please indicate excavator's name and phone number on the application.
- 2. Test holes for <u>REPAIRS and PROPERTY ALTERATIONS</u> should be dug with a backhoe when site conditions permit. <u>This is the preferred method and may be required, depending upon the site.</u> If site conditions absolutely do not permit the use of a backhoe, test holes may be dug by hand using a post-hole digger or auger. Hand-dug holes must be a minimum of 8 inches wide and 5 feet deep. All hand-dug holes should be covered to prevent freezing and/or accidents.

soilinst.wpd03/08/02

## **Instructions for Soil Evaluations**

- 1. All test holes for <u>NEW CONSTRUCTION</u> must be dug with a backhoe, by appointment <u>ONLY</u>. Please indicate excavator's name and phone number on the application.
- 2. Test holes for <u>REPAIRS and PROPERTY ALTERATIONS</u> should be dug with a backhoe when site conditions permit. <u>This is the preferred method and may be required, depending upon the site.</u> If site conditions absolutely do not permit the use of a backhoe, test holes may be dug by hand using a post-hole digger or auger. Hand dug holes must be a minimum of 8 inches wide and 5 feet deep. All hand-dug holes should be covered to prevent freezing and/or accidents.